

# CORNERED AUDIO C15NC



## FEATURES

15" long throw woofer  
 18mm plywood cabinet  
 Bass reflex design  
 Built in flying system

## COLOURS




## Description

C15NC is a high-performance subwoofer that combines very high output with low weight. Featuring a built in flying system, the C15NC is particularly suited as fly sub for the LS1 or LS2 line source. Designed for medium to high SPL applications, the plywood cabinet features a non-reflective coating, recessed dual Speakon NL4 connections, a solid 2mm foam covered steel grille and optional rubber feet.

The 15" woofer feature an advanced neodymium motor with very low power compression. The 4" four-layer interleaved voice coil provides high levels of thermal stability and the double spider ensure long linear travel and a high degree of control this reducing distortion to a minimum.

## DATA



Power handling, IEC268:	1000 watt
Power handling, peak:	4000 watt
Sensitivity, 2.83V/1m:	97 dB
Maximum SPL, long term:	127 dB
Maximum SPL, peak:	133 dB
Frequency response:	32-940 Hz
Nominal impedance:	8 ohm
Connections:	Dual Speakon NL4 with link
Measurement:	502x502x502mm
Weight:	28 kg

---

# CORNERED AUDIO C15NC

---

## Architectural Specifications

The loudspeaker system shall consist of a 15" woofer with a 4" interleaved sandwich voice coil. The cabinet shall be reflex loaded, made in plywood with integrated flying system and recessed Speakon NL4 connections.

Performance specifications of a typical production shall be as follows:

SPL at 1m with 2.83 V input shall be at least 97 dB. Nominal impedance shall be 8 ohms, with minimum impedance being 6,2 ohm @ 170 Hz. Rated power handling according to IEC 268-5 shall be at least 1000 watt.

Frequency response shall be from 32-940Hz +/- 3 dB. The enclosure shall be painted in a non-reflective coating. Outside dimensions shall be no greater than 502 mm (height) x 502 mm (width) x 502 mm (depth) and weight shall be 28 kg. The loudspeaker system shall be the Cornered Audio C15NC.

---

CORNERED Audio ApS  
Rosenkæret 13, 2. tv  
2860 Søborg  
Denmark

info@cornered.dk  
+45 43 66 10 88  
www.cornered.dk