

EMB15-4-M EMB II SERIES

15" DOWN-FIRING SUBWOOFER



Size	16 h x 16.25 w x 16.25 d (in) 406 h x 412 w x 412 d (mm)
Freq Response	18-120Hz \pm 3dB
Impedance	4 ohms
Sensitivity	93dB 2.83V /1m
Power req.	250-1000W
Woofer	(2) 15" (305mm) Aluminum Cone
Enclosure	Aluminum
Finish	Satin Black

(2) 15" Aluminum Cone Woofer (Active/Passive)

One of many available options in the EMB II Subwoofer series features a very contemporary down-firing cabinet design and a size that isn't obtrusive. Built from solid aluminum and powder coated to a fine finish, the exquisite craftsmanship of this powerful subwoofer exudes luxury and performance. The EMB15-4-M is built tough to withstand extreme weather, protecting components with sealed aircraft aluminum enclosures, powder coating, aluminum constructed domes, rubber surrounds and marine grade hardware.

Internally, the EMB15-4-M utilizes a sealed design with a James 15" high excursion woofer with a patented dual gap magnet motor for high output and low distortion. An aluminum cone, Santoprene™ half-roll surround and cast aluminum frame ensure the system is ready for outdoor and marine applications. The EMB15-4-M subwoofer has been tuned to perform beyond 35Hz, (which is predominantly where most recorded bass frequencies tend to occur) all the way down to 18Hz! Because it is a high power handling passive subwoofer, we recommend pairing it with our M1000 class D amplifier which provides 1000W of clean power and features a full DSP digital processor. You can power one EMB15-4-M subwoofer with a single M1000 amplifier.

James
LOUDSPEAKER

2185 Park Place, Minden, NV 89423
Ph: 775.461.7500
www.jamesloudspeaker.com