

O N K Y O

MUSE SERIES

Y-40

NETWORK INTEGRATED AMPLIFIER



HIGH POWER, REFINED SOUND

Featuring an Axign Class D amplifier with MOSFET outputs, the Y-40 delivers a commanding 150W (4 ohms) of power, capable of driving any speaker with authority. The Muse Series continues Onkyo's long tradition of meticulous sound craftsmanship. With its powerful yet expansive soundstage, the Y-40 faithfully conveys the artist's original intent without compromise.

COMPACT BODY AND SMART U/I

The compact form of the Muse Series integrates effortlessly into any space in your home. Its 5.46-inch color LCD offers a wealth of information, including details about the currently playing track and an analog-style VU meter. This display, combined with an intuitive interface, also simplifies adjusting the unit's settings. The Muse Series works with the Onkyo Controller app, allowing you to power the unit on or off and manage settings just as you would with other Onkyo products.

EVERYTHING YOU NEED FOR EPIC AUDIO EXPERIENCES

The Y-40 has almost all the inputs and outputs you need for an immersive audio experience. Three pairs of analog RCA analog inputs, COAX input, Phono input, HDMI ARC, and MM-compatible Phono input. It supports Ethernet and WiFi, enabling modern listening styles with streaming playback.

SUPPORTING YOUR MODERN AUDIO EXPERIENCE

Your carefully curated playlists play well with the Onkyo Y-40 Network Integrated Amplifier. Seamlessly hardwire or cast your content from any of the following built-in platforms: Spotify Connect, TIDAL Connect, Qobuz Connect, AirPlay 2, and Google Cast.

THE PERFECT AUDIO SYSTEM FOR YOU

The Y-40 has an output power of 150w(4ohm)/75w(8ohm). Although it is a compact single integrated amplifier, it can powerfully drive a wide variety of speakers, from large floor standing speakers to small bookshelf speakers, to maximize their potential.

SPECIFICATIONS

OUTPUT POWER	150w(4Ω, 1kHz, THD 0.7%, 2ch driven) / 75w(8Ω, 20Hz-20kHz, THD 0.08%, 2ch driven)
AMPLIFIER CHANNEL	2 Ch
PRE AMPLIFIER CHANNEL	2 Ch
AMPLIFIER TYPE	Class D
FREQUENCY RESPONSE	20Hz~30kHz(+1/-3dB)
tone CONTROL (BASS / TREBLE)	100Hz ±10dB / 10kHz ±10dB
SPEAKER IMPEDANCE	4-16Ω
ANALOG AUDIO INPUT	RCA (Unbalanced) x 3 Pair
DIGITAL AUDIO INPUT	HDMI ARC, COAX, Optical, USB-A (Storage playback)
PHONO INPUT	1 Pair (MM)
AUDIO PRE OUTPUT	RCA(Unbalanced) x 1 Pair
HEADPHONE OUTPUT	1/4"(6.3mm) Jack
NETWORK CONNECTIVITY	Wi-Fi, LAN
BLUETOOTH	SBC, AAC
PRODUCT DIMENSIONS (W X H X D)	13.8" (350mm) x 3.9" (99mm) x 13.3" (337mm)
PRODUCT WEIGHT	9.7lbs (4.4 kg)
PACKAGE DIMENSIONS (W X H X D)	18.3" (465mm) x 8.9" (225 mm) x 15.9" (405mm)
PACKAGE WEIGHT	CUM: 15.4lbs (7.0kg), CUP: 15.0lb (6.8kg), CUR/CUJ: 14.6lb (6.6kg)
POWER CONSUMPTION	65w, 1.8w (idle), Less than 0.4w (Standby)

MODEL NAME	REGION	EAN
Y-40(B)CUM	EU UK AU	4573211156003
Y-40(S)CUP	EU UK	4573211156010
Y-40(B)CUR	CHINA	4573211156003
Y-40(B)CUJ	JAPAN	4573211156034

(B) = Black | (S) = Silver



1-1-41 Kawamata, Higashiosaka-shi, Osaka 577-0063 Japan / Japon | ONKYO.COM