



Specification Sheet

V10+		
Specifications / features.	Values / features	Notes / Comments.
THX® Certification		
Frequency Response	24-200 Hz	(Average Response in Room +/- 3 dB)
Frequency Roll Off	24 Hz	(-6 dB 20 Hz Nearfield)
Variable Low Pass Filter	60-200 Hz	Continuesly Variable / 4th Order
Phase Control	0 - 180 deg	Continuesly Variable
Line level input/output	2 x RCA phono	Left / Right - input / output
Amplifier type		Analog input / switch mode power output
Drive unit	1 x 10"	Long Throw
System Principle		Sealed enclosure
Amplifier Power output RMS	300 watt	<0.5% THD at 300W into 4 ohms
Amplifier Power output Peak	600 watt	
Standby Power Consumption	0.5 watt	30W Average, 150W Max
Headroom Limiter Maximizer	Yes	(Dynamic driver excursion control)
Auto Power detect on/off	Yes	
Finish	Satin	Black / White
Dimensions	H x W x D	13.6 x 13.6 x 13.6 in / 345 x 345 x 345 mm
Weight	Netto	34.0 lbs / 15.4 kg
Manual	Yes	Safety Manual included in packing
Accessories	Yes	Gloves, US/EU Power cords, Rubber Feet
Version 1 - January 2022		

The Choice of Professionals™