

# SONANCE

## POWERPIPE X SERIES DATA SHEET

### PPX10

#### TECHNICAL SPECIFICATIONS

SKU	93786 - Each
Woofers	10" (254mm) anodized aluminum cone, rubber surround, high excursion
Frequency Response	39Hz - 115Hz +/-3dB
Impedance	4 ohms nominal
Sensitivity (2.83V/1m)	92dB SPL
Enclosure	MDF (Medium Density Fiberboard)
Finish	Textured Black
Recommended Power	400 watts
Recommended Amplifiers	Blaze Powerzone Connect 1502   3004   6008   Sonance DSP 2-750 MKIII
Tube Inside Diameter	4.02" (102mm)
Tube Length	21.65" (550mm)
Product Dims w/ Feet (WxHxD)	12.99" x 13.6" x 11.81" (330mm x 346mm x 300mm)
Product Dims w/o Feet (WxHxD)	12.99" x 12.99" x 11.81" (330mm x 330mm x 300mm)
Product Weight	38.27 lbs. (17.36kg)
Shipping Weight	44.75 lbs. (20.3kg)

#### ACCESSORIES

**PPX-4R | 93794**  
PPX 4" XPC Grille Connector

**PPX-6R | 93795**  
PPX 6" XPC Grille Connector

**PPX-8R | 93796**  
PPX 8" XPC Grille Connector

**PPX-6-90 | 93793**  
PPX 90-Degree Adapter

**PPX-4to6-90-ADAPTER | 93792**  
PPX 4" to 6" 90-Degree Adapter

**PPX-4to6-STR-ADAPTER | 93791**  
PPX 4" to 6" Straight Adapter

**PPX-3.5x16-2-STR | 93790**  
PPX Straight Toekick Connector and Grille

**PPX-3.5x16-2-90 | 93789**  
PPX 90-Degree Toekick Connector and Grille

**PPX TOEKICK REPLACEMENT GRILLE | 93799**  
Straight or 90-Degree Toekick Connector Required

#### DIMENSIONAL DRAWINGS

