

# SONANCE

## POWERPIPE X SERIES DATA SHEET

### PPX12

#### TECHNICAL SPECIFICATIONS

SKU	93787 - Each
Woofers	12" (305mm) anodized aluminum cone, rubber surround, high excursion
Frequency Response	34Hz - 100Hz +/-3dB
Impedance	4 ohms nominal
Sensitivity (2.83V/1m)	93dB SPL
Enclosure	MDF (Medium Density Fiberboard)
Finish	Textured Black
Recommended Power	500 watts
Recommended Amplifiers	Blaze Powerzone Connect 1502   3004   6008   Sonance DSP 2-750 MKIII
Tube Inside Diameter	5.98" (152mm)
Tube Length	25.59" (650mm)
Product Dims w/ Feet (WxHxD)	15.75" x 16.36" x 15.16" (400mm x 415mm x 385mm)
Product Dims w/o Feet (WxHxD)	15.75" x 15.75" x 15.16" (400mm x 400mm x 385mm)
Product Weight	55.87 lbs. (25.34kg)
Shipping Weight	64.37 lbs. (29.2kg)   Team lift required

#### ACCESSORIES

##### PPX-8R | 93796

PPX 8" XPC Grille Connector

##### PPX-6R | 93795

PPX 6" XPC Grille Connector

##### PPX-6-90 | 93793

PPX 90-Degree Adapter

##### PPX-3.5x16-2-STR | 93790

PPX Straight Toekick Connector and Grille

##### PPX-3.5x16-2-90 | 93789

PPX 90-Degree Toekick Connector and Grille

##### PPX TOEKICK REPLACEMENT GRILLE | 93799

Straight or 90-Degree Toekick Connector Required

#### DIMENSIONAL DRAWINGS

